

Testing: D&D vs Competitor A

Third-party, independent testing conducted by the Akron Rubber Development Laboratory, Inc.

A48			AX34		
Manufacturer	Maximum Elongation, %	Breaking Strength, lbf	Manufacturer	Maximum Elongation, %	Breaking Strength, lbf
D&D	9.93	1623	D&D	11.94	2190
Competitor A	9.07	1390	Competitor A	12.37	2060

B45			BX80		
Manufacturer	Maximum Elongation, %	Breaking Strength, lbf	Manufacturer	Maximum Elongation, %	Breaking Strength, lbf
D&D	12.13	2310	D&D	9.01	2840
Competitor A	11.02	1775	Competitor A	9.32	2500

170J6			4LK970		
Manufacturer	Maximum Elongation, %	Breaking Strength, lbf	Manufacturer	Maximum Elongation, %	Breaking Strength, lbf
D&D	12.53	1484	D&D	3.73	2940
Competitor A	11.62	1324	Competitor A	3.47	1915

Testing: D&D vs Competitor B

Third-party, independent testing conducted by the Akron Rubber Development Laboratory, Inc.

BX85E			AX50E		
Manufacturer	Maximum Elongation, %	Breaking Strength, lbf	Manufacturer	Maximum Elongation, %	Breaking Strength, lbf
D&D	8.61	3003	D&D	6.85	1814.43
Competitor B	7.51	2816.4	Competitor B	7.59	1922

B97			3VX670E		
Manufacturer	Maximum Elongation, %	Breaking Strength, lbf	Manufacturer	Maximum Elongation, %	Breaking Strength, lbf
D&D	8.90	2980	D&D	8.03	1747.6
Competitor B	8.36	3193.18	Competitor B	4.31*	742

* Low elongation is a result of premature breaking before elongation could